



## 1 5/8" Coaxial Connectors

### *MonoBlock*



ITEM NUMBER	DESCRIPTION
NM50V158MA	N-male, MonoBlock, O-ring
NF50V158MA	N-female, MonoBlock, O-ring
7/16M50V158MA	7/16 DIN male, MonoBlock, O-ring
7/16F50V158MA	7/16 DIN female, MonoBlock, O-ring

#### ELECTRICAL

- Nominal impedance,  $\Omega$  50
- Return loss @ 2.5 GHz, dB -35
- 3rd order intermodulation product, dBc -163
- Temperature range -40°F to +140°F (-40°C to +60°C)
- Water immersion testing IP67 & IP68
- Materials
  - External parts Passivated silver plated or electroless nickel plated brass
  - Outer contact Passivated silver plated brass
  - Inner contact Passivated silver plated Cu-Be
  - Dielectric TXP / PTFE
  - O-rings Silicone rubber

#### ACCESSORIES

For complete accessory, refer to Eupen Site Steel & Accessory Catalog.

DESCRIPTION	ITEM NUMBER
<b>Tools</b> (See Tool Section page 4/)	
Cable Prep Tool	F-158
Ground Kit Tool	GKT-EC7
Torque Wrench, Back Nut	TQ-214-F29
Torque Wrench, 7/16 DIN Coupler	TQ-114-F18M
<b>Hoisting Grips</b>	
Lace-Up Hoisting Grip	HG-158
Pre-Laced Hoisting Grip	HG-158L
<b>Hangers</b>	
Butterfly Hangers, Kit of 10	BH-158-NH
Snap-In Hangers, Kit of 10	SH-U158
Snap-Stack Hangers, Kit of 10	SH-S158
<b>Coax Support Blocks</b>	
Mini Coax Support Blks, Kit of 10	CB-158

DESCRIPTION	ITEM NUMBER
<b>Angle Adapters, Stainless Steel</b>	
Universal SST Angle Adaptor, Kit of 10	AA-U
SST Angle Adaptor, Kit of 10	AA-SL
<b>Grounding Kits</b>	
Standard Grounding Kit	GK-S158
Clip-On Grounding Kit	GK-C158
<b>Weatherproofing</b>	
Standard Weatherproofing Kit	WK-U
<b>Boots and Cushions</b>	
4" Boot Assembly, 1 hole	BA-158-1A
Standard Port Cushion, 1 hole	SC-158-1
4" Boot Assembly, Cushion not included	BA-400
5" Boot Assembly, Cushion not included	BA-500