



1 5/8" Coaxial Connectors

MonoBlock



ITEM NUMBER	DESCRIPTION
NM50V158MA	N-male, MonoBlock, O-ring
NF50V158MA	N-female, MonoBlock, O-ring
7/16M50V158MA	7/16 DIN male, MonoBlock, O-ring
7/16F50V158MA	7/16 DIN female, MonoBlock, O-ring

ELECTRICAL

- Nominal impedance, Ω 50
- Return loss @ 2.5 GHz, dB -35
- 3rd order intermodulation product, dBc -163
- Temperature range -40°F to +140°F (-40°C to +60°C)
- Water immersion testing IP67 & IP68
- Materials
 - External parts Passivated silver plated or electroless nickel plated brass
 - Outer contact Passivated silver plated brass
 - Inner contact Passivated silver plated Cu-Be
 - Dielectric TXP / PTFE
 - O-rings Silicone rubber

ACCESSORIES

For complete accessory, refer to Eupen Site Steel & Accessory Catalog.

DESCRIPTION	ITEM NUMBER
Tools (See Tool Section page 4/)	
Cable Prep Tool	F-158
Ground Kit Tool	GKT-EC7
Torque Wrench, Back Nut	TQ-214-F29
Torque Wrench, 7/16 DIN Coupler	TQ-114-F18M
Hoisting Grips	
Lace-Up Hoisting Grip	HG-158
Pre-Laced Hoisting Grip	HG-158L
Hangers	
Butterfly Hangers, Kit of 10	BH-158-NH
Snap-In Hangers, Kit of 10	SH-U158
Snap-Stack Hangers, Kit of 10	SH-S158
Coax Support Blocks	
Mini Coax Support Blks, Kit of 10	CB-158

DESCRIPTION	ITEM NUMBER
Angle Adapters, Stainless Steel	
Universal SST Angle Adaptor, Kit of 10	AA-U
SST Angle Adaptor, Kit of 10	AA-SL
Grounding Kits	
Standard Grounding Kit	GK-S158
Clip-On Grounding Kit	GK-C158
Weatherproofing	
Standard Weatherproofing Kit	WK-U
Boots and Cushions	
4" Boot Assembly, 1 hole	BA-158-1A
Standard Port Cushion, 1 hole	SC-158-1
4" Boot Assembly, Cushion not included	BA-400
5" Boot Assembly, Cushion not included	BA-500