



# 1/2" - Hiflex

## STANDARD

Cable type : **5092**  
Reference : **EC4-50-HF**

Cable with standard UV resistant PE jacket,  
halogen free according to IEC 60754

## CHARACTERISTICS

### Construction

<b>• Inner conductor</b>	
Material	<b>copper clad aluminium wire</b>
Diameter (mm) (in)	<b>3.55 (0.14)</b>
<b>• Dielectric</b>	
Material	<b>gas-injected cellular polyethylene</b>
Diameter (mm) (in)	<b>9 (0.35)</b>
<b>• Outer conductor</b>	
Material	<b>corrugated copper tube</b>
Diameter (mm) (in)	<b>12.1 (0.48)</b>
<b>• Outer sheath</b>	
Thickness (mm) (in)	<b>0.7 (0.03)</b>
Diameter (mm) (in)	<b>13.6 (0.54)</b>

### Mechanical characteristics

<b>• Minimum bending radius</b>	
a) single bending (cm) (in)	<b>3 (1.2)</b>
b) 15 repeated bends (cm) (in)	<b>3 (1.2)</b>
<b>• Maximum pulling strength (daN) (lb)</b>	
	<b>68 (153)</b>
<b>• Recommended temperature range</b>	
- Storage	<b>-70 to +85 °C (-94 to +185 °F)</b>
- Installation	<b>-40 to +60 °C (-40 to +140 °F)</b>
- Operation	<b>-55 to +85 °C (-67 to +185 °F)</b>
<b>• Max. length per hoisting grip (m) (ft)</b>	
	<b>70 (230)</b>
<b>• Maximum hanger spacing (m) (ft)</b>	
	<b>0.5 (1.6)</b>
<b>• Flat plate crush res. (kg/mm) (lb/in)</b>	
	<b>2.1 (121)</b>
<b>• Bending moment (Nm) (lb-ft)</b>	
	<b>2 (1.5)</b>
<b>• Approximate weight<sup>[4]</sup> (kg/km) (lb/ft)</b>	
	<b>191 (0.129) / 203 (0.137)</b>

[1] The attenuation can be approximated by the formula:

$$\alpha(f[\text{MHz}]) = A \cdot \sqrt{f[\text{MHz}]} + B \cdot f[\text{MHz}] \quad (\text{dB}/100\text{m})$$

A = 0.317  
B = 0.00068

## FLAME RETARDANT

Cable type : **5092-HLFR**  
Reference : **EC4-50-HF-FR**

Cable with UV resistant, halogen free, low smoke,  
flame retardant jacket according to IEC 60754,  
IEC 60332-1, IEC 60332-3 cat. C and IEC 61034.  
Reaction to fire according to EN 60332-1-2 E<sub>ca</sub>.  
Compliant to EN 50575.

### Electrical characteristics

• Characteristic impedance (Ω)	<b>50.3 ± 0.5</b>
• Nominal capacity (pF/m) (pF/ft)	<b>82 (25)</b>
• Relative propagation velocity (%)	<b>82</b>
• Inductance (μH/m) (μH/ft)	<b>0.204 (0.062)</b>
<b>• DC-resistance at 20°C (68°F)</b>	
- inner conductor (Ω/km) (Ω/1000ft)	<b>2.76 (0.84)</b>
- outer conductor (Ω/km) (Ω/1000ft)	<b>3.5 (1.07)</b>
• RF peak voltage (kV)	<b>1.1</b>
• RF peak power (kW)	<b>12.7</b>
• Cut-off-frequency (GHz)	<b>13.2</b>
• Insulation resistance (MΩ.km)	<b>&gt;&gt; 5000</b>
<b>• Attenuation<sup>[1]</sup> and power rating</b>	

Frequency (MHz)	Attenuation at 20°C (68°F) <sup>[2]</sup>		Mean power rating <sup>[3]</sup> (kW)
	(dB/100m)	(dB/100ft)	
10	1.01	0.308	9.45
20	1.43	0.436	6.66
30	1.76	0.537	5.43
80	2.89	0.881	3.30
100	3.24	0.988	2.94
150	3.98	1.213	2.39
200	4.62	1.409	2.06
300	5.69	1.735	1.67
400	6.61	2.015	1.44
450	7.03	2.143	1.36
500	7.43	2.265	1.28
600	8.17	2.491	1.17
700	8.86	2.701	1.08
800	9.51	2.899	1.00
894	10.09	3.076	0.95
960	10.47	3.192	0.91
1000	10.70	3.262	0.89
1500	13.30	4.055	0.72
1700	14.23	4.338	0.67
1800	14.67	4.473	0.65
1880	15.02	4.579	0.63
2000	15.54	4.738	0.61
2170	16.24	4.951	0.59
2200	16.36	4.988	0.58
2300	16.77	5.113	0.57
2400	17.16	5.232	0.56
2500	17.55	5.351	0.54
2700	18.31	5.582	0.52
3000	19.40	5.915	0.49
4000	22.77	6.942	0.42
6000	28.63	8.729	0.33

[2] Nominal values

[3] Ambient temperature = 40°C (104°F); temperature of inner conductor = 100°C (212°F);

VSWR = 1.0; no solar loading

[4] Standard PE jacket / HLFR Jacket

