



1/4" - Hiflex

STANDARD

Cable type : **5042**
Reference : **EC1-50-HF-B**

Cable with standard UV resistant PE jacket,
halogen free according to IEC 60754

CHARACTERISTICS

Construction

• Inner conductor	
Material	copper clad aluminium wire
Diameter (mm) (in)	1.9 (0.07)
• Dielectric	
Material	gas-injected cellular polyethylene
Diameter (mm) (in)	4.6 (0.18)
• Outer conductor	
Material	corrugated copper tube
Diameter (mm) (in)	6.4 (0.25)
• Outer sheath	
Thickness (mm) (in)	0.55 (0.02)
Diameter (mm) (in)	7.5 (0.3)

Mechanical characteristics

• Minimum bending radius	
a) single bending (cm) (in)	2.5 (1)
b) 15 repeated bends (cm) (in)	2.5 (1)
• Maximum pulling strength (daN) (lb)	
	30 (67)
• Recommended temperature range	
- Storage	-70 to +85 °C (-94 to +185 °F)
- Installation	-40 to +60 °C (-40 to +140 °F)
- Operation	-55 to +85 °C (-67 to +185 °F)
• Max. length per hoisting grip (m) (ft)	
	70 (230)
• Maximum hanger spacing (m) (ft)	
	-
• Flat plate crush res. (kg/mm) (lb/in)	
	1.8 (104)
• Bending moment (Nm) (lb-ft)	
	1.1 (0.8)
• Approximate weight^[4] (kg/km) (lb/ft)	
	83 (0.056) / 88 (0.06)

VSWR characteristics

• VSWR _{max}	600 - 1000 MHz	< 1.20
• VSWR _{max}	1700 - 2700 MHz	< 1.20
• VSWR _{max}	3400 - 3800 MHz	< 1.20
• VSWR _{max} ^[5]	5000 - 6000 MHz	< 1.29

[1] The attenuation can be approximated by the formula:

$$\alpha(f[\text{MHz}]) = A \cdot \sqrt{f[\text{MHz}]} + B \cdot f[\text{MHz}] \quad (\text{dB}/100\text{m})$$

A = 0.552
B = 0.0011



FLAME RETARDANT

Cable type : **5042-HLFR**
Reference : **EC1-50-HF-B-FR**

Cable with UV resistant, halogen free, low smoke,
flame retardant jacket according to IEC 60754,
IEC 60332-1, IEC 60332-3 cat. C and IEC 61034.
Reaction to fire according to EN 60332-1-2 E_{ca}.
Compliant to EN 50575.

Electrical characteristics

• Characteristic impedance (Ω)	50 ± 1.5
• Nominal capacity (pF/m) (pF/ft)	80 (24.4)
• Relative propagation velocity (%)	82
• Inductance (μH/m) (μH/ft)	0.203 (0.062)
• DC-resistance at 20°C (68°F)	
- inner conductor (Ω/km) (Ω/1000ft)	9.2 (2.8)
- outer conductor (Ω/km) (Ω/1000ft)	4.4 (1.34)
• RF peak voltage (kV)	0.6
• RF peak power (kW)	3.6
• Cut-off-frequency (GHz)	22.0
• Insulation resistance (MΩ.km)	>> 5000

• Attenuation^[1] and power rating

Frequency (MHz)	Attenuation at 20°C (68°F) ^[2]		Mean power rating ^[3] (kW)
	(dB/100m)	(dB/100ft)	
10	1.76	0.537	3.93
20	2.49	0.759	2.77
30	3.06	0.933	2.26
80	5.03	1.534	1.37
100	5.63	1.716	1.23
150	6.93	2.113	1.00
200	8.03	2.448	0.86
300	9.89	3.015	0.70
400	11.5	3.500	0.60
450	12.2	3.720	0.57
500	12.9	3.930	0.54
600	14.2	4.323	0.49
700	15.4	4.686	0.45
800	16.5	5.027	0.42
894	17.5	5.332	0.39
960	18.2	5.537	0.38
1000	18.6	5.659	0.37
1500	23.0	7.021	0.30
1700	24.6	7.509	0.28
1800	25.4	7.744	0.27
1880	26.0	7.927	0.27
2000	26.9	8.198	0.26
2170	28.1	8.567	0.25
2200	28.3	8.631	0.24
2300	29.0	8.841	0.24
2400	29.7	9.049	0.23
2500	30.4	9.253	0.23
2700	31.7	9.649	0.22
3000	33.5	10.22	0.21
4000	39.3	11.98	0.18
6000	49.4	15.05	0.14

[2] Nominal values

[3] Ambient temperature = 40°C (104°F); temperature of inner conductor = 100°C (212°F);

VSWR = 1.0; no solar loading

[4] Standard PE jacket / HLFR Jacket

[5] Maximum VSWR value for 5000 to 6000 MHz for lengths up to 5 meters