



TECHNICAL DATA SHEET

50 ohm Connectors for RF Cables

Kabelwerk | **EUPEN** AG

Rev.: 13/2017-03-14

cable

Connector 1/2" for EC4-50 (5128) and EA4-50 (5127)

FEATURES

- **Low reflection coefficient (up to 3 GHz)**
- **Low PIM level**
- **High contact force through inner contacts made in a high-strength copper alloy**
- **Watertight (IP67/IP68)**
- **Corrosion resistant**
- **Installation "fit on and tighten it"**
- **O-ring sealing**



The connectors are designed according the standard interfaces as N, 4.3/10 or DIN 7/16. Contact components are silver or trimetal plated to minimize insertion loss and passive intermodulation products; mechanical parts are nickel plated for heavy-duty handling and best corrosion resistance. Watertightness is achieved by using silicone o-rings to resist in the toughest environmental conditions. For a cost effective, easy and reliable installation, special trimming tools are recommended.

SPECIFICATIONS

| Connector type | N-male | N-female | 4.3/10 male | 4.3/10 female | 7/16 male | 7/16 female | N-male right angle | 7/16 male right angle |
|--|--|----------|-------------|---------------|-----------|-------------|--------------------|-----------------------|
| Electrical specifications | | | | | | | | |
| • Nominal impedance [Ω] | 50 | | | | | | | |
| • Return loss @ 3 GHz | ≥ 35 dB | | | | | | | |
| • Insulation resistance [$G\Omega$] | ≥ 5 | | | | ≥ 10 | | ≥ 5 | ≥ 10 |
| • Test voltage (at sea level) [kV rms, 50Hz] | 2.5 | | | | 4 | | 2.5 | 4 |
| • Working voltage (at sea level) [kV rms, 50Hz] | 1 | | | | 2.7 | | 1 | 2.7 |
| • Max. peak power [kW] | 10 | | | | 40 | | 10 | 40 |
| • Screening effectiveness up to 1 GHz [dB] | > 128 | | | | | | | |
| • Contact resistance (outer contact) [$m\Omega$] | ≤ 1 | | | | | | | |
| • Contact resistance (inner contact) [$m\Omega$] | ≤ 1 | | | | | | | |
| • PIM ratio (2 x 20 W carrier) [dBc] | ≤ -155 (Typical -163) | | | | | | | |
| Mechanical specifications | | | | | | | | |
| • Torque of coupling mechanism [Nm] | 8 | | 5 to 8 | | 30 | | 8 | 30 |
| • Tensile strength of coupling mechanism [N] | 400 | | 500 | | 1000 | | 400 | 1000 |
| • Cable retention [N] | > 500 | | > 500 | | > 1000 | | > 400 | > 700 |
| • Mechanical endurance (Nr of couplings) | ≥ 500 | | | | | | | |
| • Outer diameter [mm] | 22 | 22 | 24 | 24 | 35 | 29 | 22 | 35 |
| • Length [mm] | 61 | 59 | 59 | 66 | 59 | 60 | 54 x 40.4 | 60 x 39.5 |
| • Weight [g] | 90 | 88 | 90 | 110 | 140 | 138 | 164 | 188 |
| Environmental specifications | | | | | | | | |
| • Temperature range | -40 °C to $+85$ °C (-40 °F to $+185$ °F) | | | | | | | |
| • Degree of protection | IP67/IP68 (mated connectors) | | | | | | | |
| • Climatic & moisture resistance test | acc. ANSI/SCTE 72 2002 R2007 (-40 °C / $+60$ °C @ 75% r.h.) for 2 weeks | | | | | | | |
| • Corrosion resistance test | acc. IEC 60068-2-11-Test Ka | | | | | | | |
| • Vibration test | acc. IEC 60068-2-6 (10 to 500 Hz @ 10 G) | | | | | | | |
| Materials | | | | | | | | |
| • Externals parts | Brass with passivated silver or trimetal or nickel plating | | | | | | | |
| • Outer contact | Brass with passivated silver or trimetal plating | | | | | | | |
| • Inner contact | Passivated silver plated high-strength copper alloy and brass | | | | | | | |
| • Dielectric | TPX / PTFE | | | | | | | |
| • O-rings | High quality silicone | | | | | | | |
| Cable dimensions [mm] | | | | | | | | |
| • Inner conductor outer diameter | 4.75 to 4.85 | | | | | | | |
| • Outer conductor outer diameter | 13.6 to 13.9 | | | | | | | |
| • Jacket outer diameter | 15.6 to 16.4 | | | | | | | |
| Order codes | | | | | | | | |
| • Connector code | NM50V12 | NF50V12 | 43MV12N1 | 43FV12N1 | 716MV12N1 | 716FV12N1 | NM50VL12 | 716MVL12 |
| • Special trimming tool | SPTC50AV12 – Silver color | | | | | | | |